

-  Oil-lubricated professional - single-stage compressors with belt drive
-  Compresseurs professionnels - mono stade entraînement par courroie - lubrifiés
-  Professionelle einstufige verdichter Riemenantrieb mit schmieresystem
-  Compresores profesionales - de una sola etapa transmisión de correa - lubricados

ER EC 200/3 T



CARATTERISTICHE TECNICHE - TECHNICAL DATA

COD.	TYPE	Liters	Cil.	lt/min.	CFM	m ³ /h	bar	psi	Hp/Cv	kW	Volt/ph	r.p.m.	Kg	Lbs	A x B x h cm.
MONOFASI CARRELLATI - SINGLE PHASES/PORTABLE															
ER 91046	ER EC 50/3M*	50 C	2	315	11,1	20	9	131	3	2,2	230/1	1.400	57	125	85x38x73
ER 91042	ER EC 100/3M	100 C	2	315	11,1	20	9	131	3	2,2	230/1	1.400	67	147	108x40x79
ER 91043	ER EC 150/3M*	150 C	2	315	11,1	20	9	131	3	2,2	230/1	1.400	86	189	132x45x92
ER 91044	ER EC 200/3M	200 C	2	315	11,1	20	9	131	3	2,2	230/1	1.400	96	211	145x50x107
ER 91045	ER EC 270/3M*	270 C	2	315	11,1	20	9	131	3	2,2	230/1	1.400	112	246	155x57x118
TRIFASI CARRELLATI - THREE PHASES/PORTABLE															
ER 91047	ER EC 50/3T*	50 C	2	315	11,1	20	9	131	3	2,2	400/3	1.400	57	125	85x38x73
ER 91036	ER EC 100/3T	100 C	2	315	11,1	20	9	131	3	2,2	400/3	1.400	67	147	108x40x79
ER 91040	ER EC 150/3T*	150 C	2	315	11,1	20	9	131	3	2,2	400/3	1.400	86	189	132x45x92
ER 91037	ER EC 200/3T	200 C	2	315	11,1	20	9	131	3	2,2	400/3	1.400	96	211	145x50x107
ER 91041	ER EC 270/3T*	270 C	2	315	11,1	20	9	131	3	2,2	400/3	1.400	112	246	155x57x118

ER EC 270/4 T



CARATTERISTICHE TECNICHE - TECHNICAL DATA

COD.	TYPE	Liters	Cil.	lt/min.	CFM	m ³ /h	bar	psi	Hp/Cv	kW	Volt/ph	r.p.m.	Kg	Lbs	A x B x h cm.
TRIFASI CARRELLATI - THREE PHASES PORTABLE															
ER 91048	ER EC 100/4T	100 C	2	481	16,9	30	9	131	4	3	400/3	1.400	98	216	108x40x79
ER 91049	ER EC 150/4T*	150 C	2	481	16,9	30	9	131	4	3	400/3	1.400	113	249	132x45x92
ER 91038	ER EC 200/4T	200 C	2	481	16,9	30	9	131	4	3	400/3	1.400	123	271	145x50x107
ER 91039	ER EC 270/4T	270 C	2	481	16,9	30	9	131	4	3	400/3	1.400	139	306	155x57x118
TRIFASI FISSI - THREE PHASES															
ER 91051	ER EC 200/4TF	200 F	2	481	16,9	30	9	131	4	3	400/3	1.400	123	271	145x50x107
ER 91052	ER EC 270/4TF	270 F	2	481	16,9	30	9	131	4	3	400/3	1.400	139	306	155x57x118